

# ISUZU ELF

*NLR55 MICROBUS*

**BANYAK  
PENUMPANGNYA  
PASTI  
UNTUNGNYA**



Efisien

\* untuk engine 4JB1-TC



20 SEAT

Long Wheel Base\*

\* khusus NLR 55B LX



Hexa Pod Cabin

\*\* Ilustrasi merupakan contoh sebagian aplikasi di lapangan.

**REAL PARTNER. REAL JOURNEY.**

# SPESIFIKASI TEKNIS NLR 55 MICROBUS

DIMENSI / DIMENSION	MICROBUS NLR 55B LX AC	MICROBUS NLR 55B AC
Panjang / Overall Length [OAL]	mm 6,370	5,150
Lebar / Overall Width [OW]	mm 1,835	1,835
Tinggi / Overall Height [OH]	mm 2,530	2,470
Jarak Sumbu / Wheelbase [WB]	mm 3,360	2,490
Julur Depan / Front Overhang [FOH]	mm 1,110	1,110
Julur Belakang / Rear Overhang [ROH]	mm 1,900	1,550
Jarak Terendah ke Tanah / Minimum Clearance [HH]	mm 190	190
Jejak Depan / Front Tread [AW]	mm 1,490	1,425
Jejak Belakang / Rear Tread [CW]	mm 1,410	1,395
MESIN / ENGINE		
Model	4JB1-TC	
Tipe / Type	In-line 4 Cylinders, Direct Injection Diesel, Turbo Intercooler , OHV	
Diameter x Langkah / Bore x Stroke	mm 93 x 102	
Isi Silinder / Piston Displacement	cc 2,771	
Tenaga Maksimum / Maximum Power	PS/rpm 100 / 3,400	
Torsi Maksimum / Maximum Torque	Kgm/rpm 22.5 / 2,000 - 3,200	
TRANSMISI / TRANSMISSION		
Model	MSB5M	MSB5S
Perbandingan Gigi / Gear Ratio	1st	5.594
	2nd	2.814
	3rd	1.660
	4th	1.000
	5th	0.794
Rev	5.334	4.783
Perbandingan Gigi Terakhir / Final Gear Ratio	5.857	4.875
BERAT / WEIGHT		
Berat Total Kendaraan / Gross Vehicle Weight [GVW]	kg 5,100	5,100
REM / BRAKE		
Rem Kaki / Service Brake	Hydraulic, saluran ganda dengan vacum booster	
Rem Tangan / Hand Brake	Mekanisme expanding di transmisi belakang	
Sistem Pengereman Gas Buang / Exhaust Brake	Ada	Tidak Ada

\* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan.

KAPASITAS GARDAN / AXLE CAPACITY	MICROBUS NLR 55B LX AC	MICROBUS NLR 55B AC
Depan / Front	kg 2,550	2,550
Belakang / Rear	kg 2,550	2,550
RODA / TYRE		
Ban Depan / Front Tyre	225/75/R16	225/75/R16
Ban Belakang / Rear Tyre	225/75/R16	225/75/R16
Velg / Disc Wheel Size	16 X 7.00	16 X 7.00
SUSPENSI / SUSPENSION		
Depan / Front	Semi elliptical laminated leaf spring dengan shock absorber berdaya ganda	
Belakang / Rear	Semi elliptical laminated leaf spring dengan shock absorber berdaya ganda	
INTERIOR / INTERIOR		
Floor	Black Fabric Regency	Black Fabric Regency
Room Lamp	Ada	Ada
Seat	19+1	15+1
Reclining Seat	Ada	Ada
Safety Belt	Ada	Ada
Seat Cover	Fabric	Fabric
Air Conditioning	Ada	Ada
USB Port Charging	Ada	Ada
DVD, CD, MP3, USB, Aux In, Radio, SD Card	Ada	Ada
Footstep	Ada	Ada
Fire Exthing (APAR)	Ada	Ada
Glass Hammer	Ada	Ada
LAIN-LAIN / OTHERS		
Fuel Tank Capacity	ltr 100	75
Min. Turning Radius	m 7.4	5.1
Max. Gradeability	% 29	22
Max. Speed	km/h 108	102
Accu	V-Ah 12-60	12-60
Alternator	V-A 12-60	12-60
Alternator AC	80	80
Central Lock	Ada	Ada
Power Steering	Ada	Ada
Reverse Parking Camera	Ada	Ada

\*\* Ilustrasi merupakan contoh sebagian aplikasi di lapangan.



## EFISIEN ENGINE 100PS

Menggunakan mesin 4JB1-TC yang hemat bahan bakar untuk mendukung segala peruntukan operasional usaha serta telah memenuhi standar Euro-2.



Agan Pemegang Merek & Distributor :

**PT ISUZU ASTRA MOTOR INDONESIA**



Facebook Instagram Twitter @IsuzuID YouTube IsuzuID www.isuzu-astra.com